



Superpower Technology Company Ltd.

HK Add: Flat B, 15th Floor, Winbase Centre, 208 Queen'S Road Central, HongKong
 SZ office: 102, Cth, YangGuangXinJu, HangChen Road, GuShu, BaoAn, ShenZhen, China

Email: info@superpower.com.hk www.asound.com








QUOTATION

Not


1. price based on **MOQ/item, FOB HK or SZ**.
2. **Payment: 30% deposit in advance, the balance before shipment**
3. Warranty: 12 months after Shipment
4. Packing: Standard Retail box Package, if custom design needs to discuss

Date: 1-Feb-2010

5. Delivery : 2 weeks after P/I confirm
6. For invoice total amount less than US\$10,000.00 then shipment term will be Exwork-Shenzhen
7. Price valid: 30 Days

No.	Model No.	Description	Solution	Photo	Q'ty	Price US\$
PCI for USB & 1394 Card						
1	SP-6307-3P (QFC:60573)	VIA6307 IEEE 1394a PCI card 3+1 ports	VT6307		500	
		PCI 2.2 compliant				
		PC99 ACPI Compliant				
		Transfer rate: Each port up to 400Mbps				
		External port: 1394a x 3				
Internal port: 1394a x 1						
2	SP-6212-4P (QFC: 108594)	VIA6212 USB 2.0 PCI card 4+1 ports	VT6212		300	
		Transfer rate: Each port up to 480Mbps			1000	
		External port: USB-A x 4				
		Internal port: USB-A port x 1 (sharing with first external USB)				
3	SP-1007 (QFC: 60608)	VIA 6214 + 6307 USB 2.0 + 1394a PCI Combo card 2+2+1+1 ports	VT6214 + VT6307		300	
		External port: USB-A x 2, Internal port: USB-A port x 1				
		External port: 1394a x 2, Internal port: 1394a x 1				
		1394a: Transfer rate: Each port up to 400Mbps				
		USB 2.0: Transfer rate: Each port up to 480Mbps				
4	SP-1406	VIA 6214 + 6306 USB 2.0 + 1394a PCI Combo card 4+2+1+1 ports	VT6214 + VT6306		300	
		External port: USB-A x 4, Internal port: USB-A port x 1				
		External port: 1394a x 2, Internal port: 1394a x 1				
		1394a: Transfer rate: Each port up to 400Mbps				
		USB 2.0: Transfer rate: Each port up to 480Mbps				
PCIe for USB & 1394 Card						
1	SP-PCIeUSB20-4P	PCI-Express to USB2.0 4 ports Host Controller	MOSCHIP MS9990		300	
		1-Lane (x1) PCI-Express with transfer rate, 5Gb/s Full Duplex channel, Compliant with PCI-Express Revision 1.0a				
		Fully Plug & Play compatible, USB 2.0 EHCI and USB 1.1 OHCI compliant, Backward compatible with USB 1.1 devices				
		Data transfer rate: High Speed 480Mbps. Full Speed 12Mbps. and Low Speed 1.5Mbps supported				
		Simultaneous operation of multiple high-performance devices, Supports up to 127 devices per port				
Driver supported MS Windows 98SE/ME/2000/XP/Server 2003/Vista/7						
2	SP-PCIe1394-2P (QFC: 152109)	PCI-Express to 1394a 2+1 ports card	VIA		300	
		Compliant with PCI Express Base Specification 1.0a				
		Installs in any available PCI Express slot and supports data transfer rates up to 400Mbps				
		Two external and one internal 6-pin Firewire ports to support DV camcorders, hard disks, removable drives, scanners, digital cameras and other Firewire audio/video device				
		Fully Plug & Play and Hot Play compatible				
Driver supported MS Windows 98SE/ME/2000/XP/Server 2003/Vista/7						
3	SP-PCIe-COMBO	PCI-Express to USB 2.0 + 1394a PCI Combo card 2+2+1+1 ports	TI		300	
		1-Lane (x1) PCI-Express with transfer rate 2.5Gb/s Full Duplex channel				
		Fully Plug & Play compatible, USB 2.0 EHCI and USB 1.1 OHCI compliant, Backward compatible with USB 1.1 devices				
		Data transfer rate: High Speed 480Mbps. Full Speed 12Mbps. and Low Speed 1.5Mbps supported (for USB port)				
		Supports data transfer rates up to 400Mbps (for 1394a port)				
Driver supported MS Windows 98SE/ME/2000/XP/Server 2003/Vista/7						

4	SP-PCIeUSB30-2P (QFC: 182043)	PCI-E USB3.0 2-PORT card, NEC chip	NEC chip USB3.0		100	
		Compliant with Universal Serial Bus 3.0 specification revision 1.0				
		Supports the following speed data rates as follows: Low-speed (1.5Mbps) / Full-Speed (12Mbps) / High-Speed (480Mbps) / Super-Speed (5Gbps)				
		Supports 2 downstream ports for all speeds				
		Compliant with PCI Express Base Specification 2.0				
		Supports PCI Bus Power Management Interface Specification revision 1.2				
		System Requirement: Windows® XP/Vista/7 (32/64 bit)				
		PCI Express-enabled system with an available PCI Express slot				
PCMCIA CARD BUS for USB & 1394 Card						
1	SP-CB-USB20-2P (QFC: 48669)	2 Ports USB 2.0 Cardbus Card	VT6212		100	
		Support 32-bit CardBus Type II Slot				
		Provide 2 external USB interface ports A and an external DC power-jack 500mA of output current per port = (max)				
		Data transfer rate: High speed 480Mbps. Full speed 12Mbps and Low speed 1.5Mbps				
		Support for Windows 98SE/Me/2000/XP/Vista/7				
2	SP-CB-USB20-4P (QFC: 60611)	4 Ports USB 2.0 Cardbus Card	VT6212		100	
		Support 32-bit CardBus Type II Slot				
		Provide 4 external USB interface ports A and an external DC power-jack 500mA of output current per port = (max)				
		Data transfer rate: High speed 480Mbps. Full speed 12Mbps and Low speed 1.5Mbps				
		Support for Windows 98SE/Me/2000/XP/Vista/7				
3	SP-CB-1394-2P (QFC: 58971)	1394a * 2-port CardBus Card	VT6307		100	
		Support 32-bit CardBus Type II Slot				
		Provide 2 x 1394a ports and DC power-jack				
		Data transfer rate: 100/200/400 Mbps for 1394a port				
4	SP-CB-COMBO (QFC: 60615)	USB2.0 * 2-port and Firewire 1394a * 2-port combo CardBus Card	VIA		100	
		Support 32-bit CardBus Type II Slot				
		Provide 2 x USB 2.0 ports A, 2 x 1394a ports and DC power-jack				
		Data transfer rate: High speed 480Mbps. Full speed 12Mbps and Low speed 1.5Mbps for USB port				
EXPRESS for USB & 1394 Card						
1	SP-EC-USB20-2P	EXPRESSCARD/34mm USB2.0 x 2 PORTs Card			100	
		Provide 2 external USB interface ports A and an external DC power-jack 500mA of output current per port = (max)				
		Data transfer rate: High speed 480Mbps. Full speed 12Mbps and Low speed 1.5Mbps				
		Fully Plug & Play and Hot Play compatible				
		Support for Windows 98SE/Me/2000/XP/Vista/7				
2	SP-EC-USB20-4P	EXPRESSCARD/34mm USB2.0 x 4 PORTs Card			100	
		Provide 4 external USB interface ports A and an external DC power-jack 500mA of output current per port = (max)				
		Data transfer rate: High speed 480Mbps. Full speed 12Mbps and Low speed 1.5Mbps				
		Fully Plug & Play and Hot Play compatible				
		Support for Windows 98SE/Me/2000/XP/Vista/7				
3	SP-EC-1394-2P (QFC: 138351)	EXPRESSCARD/34mm FIREWIRE 1394a x 2 PORTs Card			100	
		Two 6-Pin 1394a Ports and an external DC 12V power-jack				
		Fully Plug & Play and Hot Play compatible				
		Data transfer rate: 100/200/400 Mbps for 1394a port				
4	SP-EC-COMBO (QFC: 128453)	EXPRESSCARD/34mm USB2.0+FIREWIRE1394a 1+2 COMBO Card			100	
		One USB2.0 Type-A connector, Two 6-Pin 1394a ports				
		External 5V DC jack for high current consumption USB devices				
		Fully Plug & Play and Hot Play compatible				
		Data transfer rate: High speed 480Mbps. Full speed 12Mbps and Low speed 1.5Mbps (for USB2.0 port), Data transfer rate: 100/200/400 Mbps (for 1394a port)				
Support for Windows 98SE/Me/2000/XP/Vista/7						

5	SP-EC-USB30-2P	EXPRESS/34mm USB3.0 2-PORT card, NEC chip	NEC chip USB3.0		100	
		Fully compliant with ExpressCard Specification 1.0				
		Compliant with Universal Serial Bus 3.0 specification revision 1.0				
		Supports USB data transfer rate of 1.5/12/480/5000 Mbps				
		Built-in DC Jack connector for receiving extra power to meet USB 3.0 +5V/900mA power output standard				
		Hot-swapping feature allows you to connect/disconnect devices without powering down the system				
		System Requirements:				
		Windows® XP/Vista/7 (32/64 bit)				
ExpressCard-enabled system with the an available ExpreeCard slot	500					